

Package: DCPO (via r-universe)

August 27, 2024

Version 0.5.4

Title Dynamic Comparative Public Opinion

Description Estimates latent variables of public opinion cross-nationally and over time from sparse and incomparable survey data. 'DCPO' uses a population-level graded response model with country-specific item bias terms. Sampling is conducted with 'Stan'. References: Solt (2020) [doi:10.31235/osf.io/d5n9p](https://doi.org/10.31235/osf.io/d5n9p).

License GPL (>=3)

Encoding UTF-8

LazyData true

ByteCompile true

Depends R (>= 3.4.0), Rcpp (>= 0.12.17), methods

Imports rstan (>= 2.26.0), rstantools (>= 2.1.0), beepr, dplyr,forcats, janitor, purrr, tibble, tidyR

LinkingTo StanHeaders (>= 2.26.0), rstan (>= 2.26.0), BH (>= 1.66.0-1), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.4.0)

Suggests knitr

SystemRequirements GNU make

NeedsCompilation yes

RoxxygenNote 7.1.2

Biarch true

Repository <https://fsolt.r-universe.dev>

RemoteUrl <https://github.com/fsolt/dcpo>

RemoteRef HEAD

RemoteSha 8f2a559f2d7e340c1889c96f4beaa8727d14cb7e

Contents

DCPO-package	2
dcpo	2
dcpo_xvt	3
demsup_data	4
extract_dcpo_results	5
get_xvt_results	6
summarize_dcpo_results	7

Index	8
--------------	----------

DCPO-package	<i>DCPO: Dynamic Comparative Public Opinion</i>
--------------	---

Description

DCPO estimates dynamic comparative public opinion as a latent variable from survey data

References

Stan Development Team (2018). RStan: the R interface to Stan. R package version 2.18.2.
<http://mc-stan.org>

dcpo	<i>Estimate Dynamic Comparative Public Opinion</i>
------	--

Description

dcpo uses diverse survey data to estimate public opinion across countries and over time.

Usage

```
dcpo(dcpo_input, chime = TRUE, ...)
```

Arguments

dcpo_input	a data frame of survey items and marginals generated by DCP0tools::dcpo_setup
chime	play chime when complete?
...	arguments to be passed to rstan::stan. Defaults reset by dcpo are described below under details.

Details

dcpo, when passed a data frame dcpo_input of survey marginals created by dcpo_setup, estimates a latent variable of public opinion. See rstan::stan for additional options; stan defaults reset by dcpo are seed = 324, thin = 2, cores = min(stan_args\$chains, parallel::detectCores()/2), and control <- list(adapt_delta = 0.99, stepsize = 0.005, max_treedepth = 14)

Value

a stanfit object

Examples

```
out1 <- dcpo(demsup_data,
              chains = 1,
              iter = 300) # 1 chain/300 iterations for example purposes only; use defaults
```

dcpo_xvt

*Cross-validation testing for DCPO***Description**

`dcpo_xvt` performs a single cross-validation test for DCPO

Usage

```
dcpo_xvt(
  dcpo_input,
  fold_number = 1,
  number_of_folds = 10,
  fold_seed = 324,
  chime = TRUE,
  ...
)
```

Arguments

<code>dcpo_input</code>	a data frame of survey items and marginals generated by <code>DCP0tools::dcpo_setup</code>
<code>fold_number</code>	an integer indicating the number of the fold to treated as test data in the current analysis
<code>number_of_folds</code>	an integer indicating the total number of folds
<code>fold_seed</code>	a seed for reproducibly randomly assigning observations to folds; when a complete set of k-fold cross-validations is to be performed, the same seed should be used for all
<code>chime</code>	play chime when complete?
<code>...</code>	arguments to be passed to <code>rstan::stan</code> . See <code>dcpo</code> .

Details

`dcpo_xvt` performs a single cross-validation test of a DCPO estimation. To perform a complete k-fold cross-validation, call it repeatedly, changing only the `fold_number` argument.

Value

a stanfit object

Examples

```
# Single cross-validation test with 25% test set
demsup_xvtest_25pct <- dcpo_xvt(demsup_data,
                                    number_of_folds = 4,
                                    iter = 300,
                                    chains = 1) # 1 chain/300 iterations for example only; use defaults
```

demsup_data

*Support for Democracy in 51 Survey Datasets***Description**

A dataset containing the prices and other attributes of almost 54,000 diamonds.

Usage

demsup_data

Format

A list of 15 elements

K an integer, the total number of countries in the data

T an integer, the total number of years in the data

Q an integer, the total number of distinct survey questions in the data

R an integer, the maximum number of response cutpoints in any survey question in the data

N an integer, the number of KTQR observations

kk a numeric vector of length N, the country of each observation

tt a numeric vector of length N, the year of each observation

qq a numeric vector of length N, the question of each observation

rr a numeric vector of length N, the response cutpoint of each observation

y_r a numeric vector of length N, the number of respondents who provided a response above the relevant cutpoint for each observation

n_r a numeric vector of length N, the total number of respondents for each observation

fixed_cutp a QxR matrix, a truth table indicating the question-cutpoint to be fixed at difficulty .5

use_delta a QxK tibble, a truth table indicating whether item difficulty should be estimated to vary by question-country to account for potential item-response bias

data an Nx14 tibble, the aggregate survey response dataset in its original format

data_args a list of length 3, indicating the arguments passed to DCPOtools::format_dcpo to generate demsup_data from demsup_data\$data

Details

Data on aggregate support for democracy reported in 51 survey datasets in 998 country-years, formatted for use with the functions of the DCPO package

Source

demsup_data replicates the data employed in Claassen, Christopher. 2019. "Estimating Smooth Country-Year Panels of Public Opinion." Political Analysis 27(1):1-20. See <https://github.com/fsolt/DCP0tools>.

extract_dcpo_results *Extract DCPO Results*

Description

extract_dcpo_results is a convenience function that extracts the main parameters of a DCPO stanfit object along with the relevant identifying information (country, year, question, and cutpoint).

Usage

```
extract_dcpo_results(  
  dcpo_input,  
  dcpo_output,  
  pars = c("theta", "sigma", "alpha", "beta", "delta"),  
  probs = c(0.1, 0.9)  
)
```

Arguments

dcpo_input	the data frame of survey items and marginals generated by DCP0tools::dcpo_setup previously passed to DCPO::dcpo to generate the stanfit object passed as dcpo_output
dcpo_output	a stanfit object output by DCPO::dcpo
pars	a character vector of parameter names to be summarized from the DCPO model: theta (mean public opinion), sigma (polarization in public opinion), alpha (question dispersion), beta (question-cutpoint difficulty), and/or delta (country-specific question bias)
probs	a numeric vector of quantiles of interest; the default is c(.1, .9)

Value

a tibble

Examples

```
out1 <- dcpo(demsup_data,
              chime = FALSE,
              chains = 1,
              iter = 300) # 1 chain/300 iterations for example purposes only; use defaults

theta_results <- summarize_dcpo_results(dcpo_input = demsup_data,
                                         dcpo_output = out1,
                                         pars = "theta")
```

get_xvt_results	<i>Get results of DCPO cross-validation testing</i>
-----------------	---

Description

`get_xvt_results` performs a single cross-validation test for `dcpo`'s estimates of cross-national public opinion

Usage

```
get_xvt_results(dcpo_xvt_output, ci = 80)
```

Arguments

<code>dcpo_xvt_output</code>	output from a single call to <code>DCPO::dcpo_xvt</code> or a k-fold test list of such output generated by <code>purrr::map</code>
<code>ci</code>	an integer indicating the desired width of credible interval for coverage testing; 80 is the default.

Value

a stanfit object

Examples

```
# Single cross-validation test with 25% test set
demsup_xvtest_25pct <- dcpo_xvt(demsup_data,
                                    chime = FALSE,
                                    number_of_folds = 4,
                                    iter = 300,
                                    chains = 1) # 1 chain/300 iterations for example only; use defaults

get_xvt_results(demsup_xvtest_25pct)
```

summarize_dcpo_results

Summarize DCPO Results

Description

`summarize_dcpo_results` is a convenience function that produces summary statistics of the main parameters of a DCPO stanfit object along with the relevant identifying information (country, year, question, and cutpoint).

Usage

```
summarize_dcpo_results(  
  dcpo_input,  
  dcpo_output,  
  pars = c("theta", "sigma", "alpha", "beta", "delta"),  
  probs = c(0.1, 0.9)  
)
```

Arguments

<code>dcpo_input</code>	the data frame of survey items and marginals generated by <code>DCPOtools::dcpo_setup</code> previously passed to <code>DCPO::dcpo</code> to generate the <code>stanfit</code> object passed as <code>dcpo_output</code>
<code>dcpo_output</code>	a <code>stanfit</code> object output by <code>DCPO::dcpo</code>
<code>pars</code>	a character vector of parameter names to be summarized from the <code>DCPO</code> model: <code>theta</code> (mean public opinion), <code>sigma</code> (polarization in public opinion), <code>alpha</code> (question dispersion), <code>beta</code> (question-cutpoint difficulty), and/or <code>delta</code> (country-specific question bias)
<code>probs</code>	a numeric vector of quantiles of interest; the default is <code>c(.1, .9)</code>

Value

a tibble

Examples

Index

* datasets

demsup_data, [4](#)

DCPO (DCPO-package), [2](#)

dcpo, [2](#)

DCPO-package, [2](#)

dcpo_xvt, [3](#)

demsup_data, [4](#)

extract_dcpo_results, [5](#)

get_xvt_results, [6](#)

summarize_dcpo_results, [7](#)